GT5 SUBWOOFERS

For more than 60 years, JBL has been delivering products embodying the technology developed in the professional arena – equipping leading recording studios and movie theaters, as well as live-music reinforcement in venues ranging from dance clubs to Woodstock. We continue to transform this expertise into products that provide the impact and excitement of a live performance. The JBL® experience is for enthusiasts who won't settle for anything less than "live" at home or on the go.

JBL GT5 subwoofers deliver best-in-class performance for those looking to add bump in the trunk. Three component subwoofers, from 10" to 15" (250mm to 380mm), are available in the GT5 lineup.

PROGRESSIVE SPIDER

Each GT5 subwoofer features a progressive spider, which offers better control at the excursion limits than the linear spider commonly used by our competitors. This progressive spider reduces distortion at high output levels.

VENTED POLEPIECES

These provide additional cooling to the motor structure, resulting in an increase in the subwoofers' thermal power-handling capability.

GT5-10

10" (250mm) Single-Voice-Coil Subwoofer

- Power handling, RMS: 275 watts
- · Power handling, peak: 1100 watts
- Frequency response: 30Hz 500Hz
- Sensitivity: 88dB
- Impedance: 4 ohms
- Polypropylene woofer cone
- I-beam basket
- Progressive spider
- Hi-roll rubber surround
- Mounting depth: 5-15/16" (151mm)

GT5-10D

10" (250mm) Dual-Voice-Coil Subwoofer

- Power handling, RMS: 275 watts
- Power handling, peak: 100 watts
- Frequency response: 30Hz 500Hz
- Sensitivity: 91dB
- Impedance: 2 or 8 ohms
- Polypropylene woofer cone
- I-beam basket
- Progressive spider
- Hi-roll rubber surround
- Mounting depth: 5-15/16" (151mm)

GT5-12

12" (300mm) Single-Voice-Coil Subwoofer

- Power handling, RMS: 275 watts
- Power handling, peak: 1100 watts
- Frequency response: 27Hz 450Hz
- Sensitivity: 90dB
- Impedance: 4 ohms
- Polypropylene woofer cone
- I-beam basket
- Progressive spider
- Hi-roll rubber surround
- Mounting depth: 6-7/16" (164mm)

GT5-12D

12" (300mm) Dual-Voice-Coil Subwoofer

- Power handling, RMS: 275 watts
- Power handling, peak: 1100 watts
- Frequency response: 27Hz 450Hz
- Sensitivity: 93dB
- Impedance: 2 or 8 ohms
- Polypropylene woofer cone
- I-beam basket
- Progressive spider
- Hi-roll rubber surround
- Mounting depth: 6-7/16" (164mm)

GT5-15

15" (380mm) Single-Voice-Coil Subwoofer

- Power handling, RMS: 300 watts
- Power handling, peak: 1200 watts
- Frequency response: 25Hz 400Hz
- Sensitivity: 92dB
- Impedance: 4 ohms
- Polypropylene woofer cone
- I-beam basket
- Progressive spider
- Hi-roll rubber surround
- Mounting depth: 7-5/16" (185mm)

IJBL

THE OFFICIAL BRAND OF LIVE MUSIC.

Harman Consumer Group, Inc. 8500 Balboa Blvd.

Northridge, CA 91329 USA 516.255.4JBL (4525) Fax: 516.682.3556

www.jbl.com

Harman International

Features, specifications and appearance a change without notice.

JBL is a registered trademark of Harman Internation Industries, Incorporated. GT Series is a trademark of Harman International Industries, Incorporated.

Designed, edited and digitally produced by the Harman Consumer Group Brand Services Department Northridge, CA.

© 2009 Harman International Industries, Incorporat All rights reserved. Part No. GT5SUBPI3/08

